



AE 3TL 1000 Series

Three-Phase Transformerless String Inverters

The AE 3TL 1000 Series adds broader functionality and system voltage options to a proven, robust design with over 3 GW installed worldwide. It is a well established product with a great reliability track record. The AE 3TL also is lightweight and easy to install. With a peak efficiency over 98% and versatile monitoring options, this is the string inverter of choice for project developers, site designers and installers.

The AE 3TL is designed with many different applications in mind. These high-quality inverters can be used for commercial rooftop and carport installations, as well as solar power plants. With a power range of 12 to 23.2 kilowatts, the AE 3TL is situated to serve installations large and small. The AE 3TL optimizes space in the site design, allowing for placement within the array, saving site owners highly valued space.

Highly precise MPP tracking combined with AE advanced monitoring solutions gives solar stakeholders the vital data needed to operate and maintain a highly efficient site, providing maximum return for investors in solar energy.

AE listens carefully to customer demands. The AE 3TL is fully compliant to NEC 2011 with standard serviceable "touch-safe" fuses and optional AFCI. The 1000 VDC input enables a reduction of BoS costs due to longer strings, fewer home runs, and lower resistive losses. Weighing just over 100 pounds, the easily installed inverter is very well suited for rooftop or space-constrained installations. Additional savings are recognized with lowered shipping costs, and there is no need for the heavy machinery associated with installing larger, heavier inverters. Arrays designed with AE 3TL string inverters have best-in-class uptime, system yields, and problem resolution.

AE Solar Energy is a US based company.



Versatility

- Wide range of output power allows for integration on a variety of site designs, with an emphasis on design flexibility and project yield.
- Superior efficiency, low shipping costs, and distributed design offer solar stakeholders increased return on investment and reduced upfront costs.
- Maximizes space for energy production
- Optional AFCI
- Unprecedented 1.75 DC:AC ratio enables lowest inverter cost per DC Watt.

Reliability

- 3 GW installed worldwide
- Proven reliability
- Low maintenance
- Improved system uptime

Superior installability

- Lightweight, easy to install
- Less space needed on site
- Lowered balance of system (BoS) costs
- Inverters closer to array

Lightweight design supports ease of installation

Maximizes project space and energy production

Highly reliable and efficient; Saves money on maintenance costs and improves energy harvest

Lower initial system costs for projects under 400 kW

Wide range of output power allows for integration on a variety of site designs



AE 3TL 1000 Series Summary Specifications*

Mechanical	AE 3TL-12	AE 3TL-16	AE 3TL-20	AE 3TL-23
Dimensions	21"(W) x 35"(H) x 11"(D) (535 x 895 x 280 [mm])			
Weight	108 lb (49 kg)			
Environmental Rating	NEMA 4/ connection box NEMA 3R			
DC Input Power Connectors	Terminal block 8-12 AWG			
AC Output Power Connectors	Terminal block 6-10 AWG			
User Interface	LCD			
Electrical				
DC Inputs				
Maximum DC Input Power**	21 kW	28 kW	35 kW	40.6 kW
Maximum Input Voltage	1000 V			
Array Configuration	Ungrounded			
Maximum Operating Input Current	27.5 A	33 A	37.5 A	40 A
Maximum Short Circuit Current (Isc)	76 A			
MPPT Voltage Range	250 V to 900 V			
Minimum Voltage for Full Power	450 V	500 V	550 V	600 V
Open-Circuit Turn-On Voltage	200 V			
Number of Strings	6			
AC Output				
Continuous Output Power	12 kW	16 kW	20 kW	23.2 kW
Operating Voltage Range	423 to 528 V			
Rated Apparent Power	12 kVA	16 kVA	20 kVA	23.2 kVA
Electrical Service Compatibility	3 AC 480 V Wye +N			
Maximum Continuous Current	14.5 A	19.3 A	24.1 A	27.9 A
Short-Circuit Fault Current	16.5 A; duration < 10 msec	21 A; duration < 10 msec	26 A; duration < 10 msec	29 A; duration < 10 msec
Nominal Frequency	60 Hz (57 Hz to 63 Hz adjustable)			
Total Harmonic Distortion	< 3%			
Efficiency				
Peak Efficiency	98.2%			
Weighted Efficiency (CEC Method)	97.5%	97.5%	97.5%	98%
Standby Losses	< 0.5 W			
Inverter Controls and Monitoring				
Anti-Islanding	In accordance with IEEE 1547 and UL 1741			
Reactive Power and Power Factor	±0.99 standard, settable from ±0.90			
Inverter Monitoring				
Communication Interfaces and Protocols	Ethernet, RS-485			
Environmental				
Operating Ambient Temp. Range**	-13°F to +131°F (-25°C to +55°C)			
Standby/Storage Ambient Temp. Range	-22°F to +158°F (-30°C to +70°C)			
Cooling	Natural convection			
Relative Humidity	95% before derating			
Elevation	6500' before derating			
Noise Emission	45 dBA at 16.5'			
Regulatory				
Agency Approvals / Regulatory Compliance	UL 1741, 1699B, IEEE 1547, CSA C22.2, FCC Part 15 (Class A and B)			
Inverter Warranty	5 years standard, extendable to 20 years			
Model Numbers Without AFCI	AE_3TL-12_10-08	AE_3TL-16_10-08	AE_3TL-20_10-08	AE_3TL-23_10-08
Model Numbers With AFCI	AE_3TL-12_10	AE_3TL-16_10	AE_3TL-20_10	AE_3TL-23_10

Options

- 5, 10, and 15 year warranty extension; Extensions are optional.
- Premium monitoring solutions
- AFCI

Subject to change without notice. Refer to user manual for detailed specification.

*Not all performance window specifications can be achieved simultaneously. Performance varies per site.

**Derating at temperatures > 122°F (50°C) for the 12 kW and 16 kW; > 113°F (45°C) for 20 kW; > 104°F (40°C) for 23 kW
Consult your AE sales or service representatives for specific PV system design questions at sales.support@aei.com.



Advanced Energy Industries, Inc.
1625 Sharp Point Drive • Fort Collins, CO 80525 U.S.A.
www.advanced-energy.com
800.446.9167 • sales.support@aei.com • invertersupport@aei.com

© Advanced Energy Industries, Inc.
All rights reserved. Printed in U.S.A.
ENG-AE3TL-1000V-250-07 4/14